

**Cable set** 

**July 2022** 

Manual-Version: 1.5 Article number: 1405

## **Content**

1	Introduction		. 3
	1.1	About this document	3
2	Wa	rranty and safety	. 4
	2.1	Warranty and safety information	. 4
		Cable set from 1000BASE-T1 MediaConverter	
4	Cor	ntact	7

#### 1 Introduction

#### 1.1 About this document

This document describes the cable set of 1000BASE-T1 MediaConverter.

For the latest version of this document please contact Technica Engineering via technicalsales@technica-engineering.de

©2022 Technica Engineering GmbH

The content in this document is copyrighted by Technica Engineering GmbH. Copying or reproducing its content in full or in parts is not allowed. Technical contents in this document are subjected to change without prior notice. Third-party contents and trademarks are the property of the corresponding vendors.

### 2 Warranty and safety

### 2.1 Warranty and safety information



Before operating the device, read this manual thoroughly and retain it for your reference.

The latest documentation for the 1000BASE-T1 Media Converter can be downloaded <a href="here">here</a>.



The power cable can be used up to a maximum of 8 Ampere of current. For such high current parallel use of a fuse and/or overcurrent protection is recommended.

Use only in dry conditions.

Do not insert any foreign object in the slots/openings of the housing. Do not apply power to a damaged device.

The device may only be used by specialists.



Do not open the device. Otherwise, the warranty will be lost.




This product is intended for use in automotive-test environments. An automotive-test environment includes test setups or test benches in the office, laboratory, and workshop areas. In the test setups, the same environmental conditions apply as in-vehicle electrical systems. Technica Engineering products are not intended to be used as standard IT equipment. The test systems and products from Technica Engineering are designed as a customer and application-specific test modules that are only used by specialists for the development and test facilities.

When integrating the modules in a vehicle or test set-up, the user must ensure appropriate ventilation or air convection.

Technica Engineering products must not be considered as a safety element out of context when using safety-critical systems and must be included in the safety assessment when used. The development class in a safety system must be taken into account with standard QM referred to as ISO26262.







Do not cover the device due to fire danger.

Do not place the device near highly flammable materials due to fire danger.

Do not use the device above the specified operating temperature. The operating temperature is the ambient temperature of the installation space.



This symbol is only valid in the European Union. If you wish to discard this product, please contact your local authorities or dealer and ask for the correct method of disposal. Technica Engineering GmbH is registered as the manufacturer of the brand "Technica Engineering" and the device type "Small devices of Information- and Telecommunications- technology for exclusive use in non-private Households". WEEE reg. No. DE 20776859

# 3 Cable set from 1000BASE-T1 MediaConverter

The cable set from 1000BASE-T1 MediaConverter includes:

Product Description	Photo	Quantity
Tyco Nano Housing for female terminals 20 position black Co: TE Connectivity Part no:2141404-1	224(224)	1
1 m Twist-Pair red/black cable 0,35mm		1
1m BR-twist a pair of cable		1
Black banana plug adapter 4mm Red banana plug adapter 4 mm		1 unit of each piece
Gold Connector Banana Plugs 4mm		2
MQS Nano Socket Contact 0,35mm Co: TE Connectivity Part no: 0968075-2		14 pieces

#### **4 Contact**

If you have any questions regarding this product, please feel free to contact us:

Technica Engineering GmbH Leopoldstr. 236 80807 München Germany

Technical support:

support@technica-engineering.de

General information:

Info@technica-engineering.de

Most current user manuals and product information:

https://technica-engineering.de/en/